







CV 30 HV - HIGH VACUUM



STEELWORKS AND FOUNDRIES



CEMENT



POWER PLANTS











SUCTION UNIT		
Voltage	V - Hz	400 - 50 3~
Power	kW	30
Electrical protection	IP	55
Max water lift	mmH□O	7.500
Max air flow	m³/h	1.300
Suction inlet	mm	140
Safety filter		70.000 - M
Cooling filter	cm² - Classe	70.000 - M

VOLUME		
Dimensions	cm	114x124x147h
Weight	kg	730

- ✓ Sturdy vacuum cleaner for intensive use
- $\checkmark\,$ Powerful lobe pump with electric motor
- ✓ High performances and long-lasting equipment
- ✓ Low noise level
- ✓ Complete steel construction
- ✓ Easy and safe to maintain





The suction unit is provided with a volumetric vacuum pump with tri-lobe rotors and lateral injection cooling system. This pump can reach very high airflow and waterlift levels

A safety filter guarantees the maximum protection for both motor and pump

A soundproof painted steel cabin with cooling fan protects the pump from external agents

The unit must be coupled with a filter hopper



- ✓ POWER CABLE AND PLUG
- ✓ CONTROL PANEL WITH PLC FOR MANAGEMENT OF EXTERNAL DEVICES (FILTER CLEANING CONTROL, PROBES, VALVES, ETC)