

## 201 DS BL - INDUSTRIAL SINGLE PHASE



- ✓ Complete steel construction
- ✓ Compact and mobile
- ✓ Simultaneous suction of solid, dust and liquid material
- ✓ Accessory kit included



### SUCTION UNIT

Power	kW	1,1
Max water lift	mmH <sub>2</sub> O	2.250
Max air flow	m <sup>3</sup> /h	215
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	76



### FILTER UNIT

Filter Type	Cartridge
-------------	-----------



### COLLECTION UNIT

Transport capacity	kg/h	20
--------------------	------	----



### VOLUME

Dimensions	cm	57X48X115 h
Weight	kg	32



## SUCTION UNIT

The motor head is equipped with a Brushless motor: the lack of carbons allows the use of the machine even in explosive hazardous areas. The motor is protected by a series of filters and it is turned on by an independent switch placed on a soundproofed and robust metal motor head.

The motor head includes a vacuum gauge and tension power lights as standard.



## FILTER UNIT

The polyester cartridge filter placed inside the filter chamber guarantees a large filter surface and prevents the clogging of the filter.



## COLLECTION UNIT

The unit is manufactured with thick painted steel for improved sturdiness and long-lasting lifetime



## OPTIONALS

- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ EARTH GROUNDING