54







451 DS BL - INDUSTRIAL SINGLE PHASE





316 X 461





Weight

- ✓ Complete steel construction
- ✓ Compact and mobile

- ✓ Simultaneous suction of solid, dust and liquid material
- ✓ Accessory kit included

CUCTION LINE		
SUCTION UNIT		
Power	kW	1,1
Max water lift	mmH□O	2.250
Max air flow	m³/h	215
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	76
FILTER UNIT		
Filter Type		Star
COLLECTION UNIT		
Transport capacity	kg/h	45
VOLUME		
Dimensions	cm	58x63x110 h

kg





SUCTION UNIT

The motor head is equipped with a Brushless motor: the lack of carbons allows the use of the machine even in explosive hazardous areas. The motor is protected by a series of filters and it is turned on by an independent switch placed on a soundproofed and robust metal motor head.

The motor head includes a vacuum gauge and tension power lights as standard.



FILTER UNIT

The large surface star antistatic filter, located inside the filter chamber, is made of polyester and provides high resistance against clogging and passage of fine dust.



COLLECTION UNIT

The unit is manufactured with thick painted steel for improved sturdiness and long-lasting lifetime



- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ EARTH GROUNDING