



# MTL 201 1/3D - ATEX EXPLOSION PROOF



CEMENT



CERAMICS AND POTTERY INDUSTRIES



BUILDING AND CONSTRUCTION



- ✓ Largest surface filter in its category
- ✓ Tangential suction inlet with integrated separation cyclone
- ✓ Complete steel construction
- ✓ Compact and mobile
- ✓ Easy filter replacement
- ✓ Stainless steel AISI304 collection tank
- ✓ Dustop filter cleaning system

## SUCTION UNIT

Atex zones	ATEX Z20/21 Z1-2	
Voltage	V - Hz	230 - 50/60 1~
Power	kW	1,15
Max water lift	mmH <sub>2</sub> O	2500
Max water lift	mmH <sub>2</sub> O	2500
Max air flow	m <sup>3</sup> /h	180
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	74
Marking	II 1/3D Ex h tb IIIC T80°C (Int) /T95°C (ext) Da/Dc	

## FILTER UNIT

Filter Type	Cartridge	
Surface - Diameter	cm <sup>2</sup> -mm	30.000 - 360
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Cleaning system	Dustop	

## COLLECTION UNIT

Transport capacity	kg/h	20
--------------------	------	----

## VOLUME

Dimensions	cm	57x48x115h
Weight	kg	32

COPYRIGHT © 2023 DELFIN S.R.L. ALL RIGHTS RESERVED  
COPYRIGHT © 2023 DELFIN S.R.L. TUTTI I DIRITTI RISERVATI



## SUCTION UNIT

The suction is made by a carbon brush by-pass motor which is activated by an independent switch placed inside a robust metal motor head. The motor head is soundproofed by sound-absorbent material.



## FILTER UNIT

A vacuum gauge enables to check constantly the state of the filter and detect possible clogging, warning the operator that the filter must be cleaned.

It is possible to clean the filter using the Dustop, an integrated reverse pulse system: by closing the suction inlet and opening a flap in the filter chamber, the airflow generated by the motor cleans the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.

The antistatic polyester cartridge filter placed inside the filter chamber guarantees a large filter surface and prevents the clogging of the filter.



## COLLECTION UNIT

The vacuumed material is placed inside an AISI304 stainless steel drop-down bin mounted on wheels, which makes it possible to dispose easily and safely of the vacuumed material.