

DG 30 EXP Z22 - ATEX EXPLOSION PROOF



FOOD INDUSTRY



ALUMINUM AND PVC



METALWORKING



VEHICLE - TRANSPORT CLEANING







Material - Efficiency

Cleaning system

- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- ✓ Integrated filter cleaning system
- ✓ Complete steel construction
- ✓ Vacuum gauge to detect filter clogging

- ✓ Reduced downtime of machine tools
- ✓ Atex certified for Zone 22
- ✓ Earth grounding

SUCTION UNIT		
Atex zones		ATEX Z22
Marking		Ex II 3D Ex tc IIIB T135°C X Dc
Voltage	V - Hz	400-50 3~
Power	kW	3
Electrical protection	IP	55
Max water lift	mmH□O	3000
Max air flow	m³/h	300
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	71
FILTER UNIT		
Filter Type		Star
Surface - Diameter	cm²-mm	20.000-500

COLLECTION UNIT		
Capacity	lt	100
VOLUME		
Dimensions	cm	66x118x145h
Weight	kg	125

IEC 60335-2-69

Polyester - ANT M

Manual





SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.



FILTER UNIT

A vacuum gauge enables to check constantly the state of the filter and detect possible clogging, warning the operator that the filter must be cleaned.

It is possible to clean the filter using an integrated mechanical system: an external lever shakes the filter vertically and enables to clean the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.



COLLECTION UNIT

The detachable AISI 304 steel collection tank has a quick release system for the rapid disposal of the vacuumed material.



OPTIONALS

- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ HEAT RESISTANT FILTER (UP TO 250° CELSIUS)
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- TOTAL STAINLESS STEEL CONSTRUCTION
- ✓ CYCLONE FOR FILTER PROTECTION
- ✓ REMOTE CONTROL
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST