

DG 300 HD EX 1/2D - ATEX EXPLOSION PROOF



AVIATION




FOOD INDUSTRY



CHEMICAL-PHARMACEUTICAL



METALWORKING



- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- ✓ Integrated filter cleaning system
- ✓ Tangential suction inlet with integrated separation cyclone
- ✓ Pressure relief valve for motor protection
- ✓ ATEX certified for Zone 20 inside the chamber and for Zone 21 outside the chamber
- ✓ Large surface antistatic filter
- ✓ Conceived for fine and hazardous dust suction
- ✓ Additional HEPA filter (99,995% on 0,18 micron) included
- ✓ Stainless steel AISI304 collection tank



SUCTION UNIT

Power	kW	18,5
Electrical protection	IP	65
Max water lift	mmH ₂ O	1800
Max water lift	mmH ₂ O	1800
Max air flow	m ³ /h	2050
Suction inlet	mm	120
Noise level (EN ISO 3744)	dB(A)	78
Atex zones		20



FILTER UNIT

Filter Type	Star
Cleaning system	Automatic AUT



SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It is designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.

A pressure relief valve protects the motor, providing additional air for cooling.

The suction unit is ATEX certified.



FILTER UNIT

The filter is equipped with an automatic filter shaking system. A pneumatic cylinder periodically shakes the star filter by a vertical shaking movement which causes the detachment of dusts and wastes from the filter. The frequency and length of this system can be adjusted by means of a timer placed inside the electrical panel.

An antistatic polyester star filter is placed inside the steel filter chamber. This filter protects the suction unit by preventing any spark which might be caused by electrostatic discharge.

A HEPA filter is included as standard (99,995% on 0,18 micron, class H) which holds the finest dusts and guarantees the cleanliness of the leaving air.



COLLECTION UNIT

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels, that make it suitable for mobile service even when used on rough surfaces.

The vacuumed material is placed inside an AISI304 stainless steel drop-down bin mounted on wheels, which makes it possible to dispose easily and safely of the vacuumed material, if need be collecting it directly into a paper bag.



OPTIONALS

- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER