220



## **DG 300 SE Z22 - ATEX EXPLOSION PROOF**



CEMENT



CHEMICAL-PHARMACEUTICAL



**BUILDING AND CONSTRUCTION** 



N\_

MINE









Transport capacity

- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- ✓ Integrated filter cleaning system
- ✓ Tangential suction inlet with integrated separation cyclone
- ✓ Complete steel construction
- ✓ Extractable collection container with optional use of disposable bags

- ✓ Vacuum gauge to detect filter clogging
- ✓ Star-triangle switchboard
- ✓ Atex certified for Zone 22
- ✓ Large surface antistatic filter
- ✓ Suitable for high specific weight material

| SUCTION UNIT              |       |               |
|---------------------------|-------|---------------|
| Power                     | kW    | 20            |
| Electrical protection     | IP    | 65            |
| Max water lift            | mmH□O | 6000          |
| Max water lift            | mmH□O | 6000          |
| Max air flow              | m³/h  | 1100          |
| Suction inlet             | mm    | 120           |
| Noise level (EN ISO 3744) | dB(A) | 77            |
| FILTER UNIT               |       |               |
| Filter Type               |       | Star          |
| Cleaning system           |       | Automatic AUT |
| COLLECTION UNIT           |       |               |

| VOLUME     |    |             |
|------------|----|-------------|
| Dimensions | cm | 92x220x220h |
| Weight     | kg | 760         |

kg/h





## **SUCTION UNIT**

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.



## **FILTER UNIT**

The large surface star filter, located inside the filter stainsteel chamber, is made of polyester and provides high resistance against clogging and passage of fine dust. The filter is equipped with an automatic filter shaking system. A pneumatic cylinder periodically shakes the star filter by a vertical shaking movement which causes the detachment of dusts and wastes from the filter. The frequency and length of this system can be adjusted by means of a timer placed inside the elecrical panel



## **COLLECTION UNIT**

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels, that make it suitable for mobile service even when used on rough surfaces. The vacuumed material is collected into a wheeled steel detachable container, which can be extracted for easy disposal and can be used with optional disposable bags, for safer and handier disposal.



- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ EARTH GROUNDING
- ✓ REMOTE CONTROL
- FORK LIFT INTAKES
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST