



#### DG VL 150 SE Z22 - INDUSTRIAL THREE PHASE





CERAMICS AND POTTERY INDUST



CHEMICAL-PHARMACEUTICAL



BUILDING AND CONSTRUCTION

- ✓ Integrated filter cleaning system
- ✓ Tangential suction inlet with integrated separation cyclone
- ✓ Extractable collection container with optional use of disposable bags
- $\checkmark$  Pressure relief valve for motor protection
- ✓ Vacuum gauge to detect filter clogging



- ✓ Star-triangle switchboard
- $\checkmark$  Easy filter replacement
- $\checkmark\,$  Atex certified for Zone 22
- $\checkmark\,$  Suitable for high specific weight material

SUCTION UNIT		
Power	kW	17,3
Electrical protection	IP	65
Max water lift	mmH□O	6.000
Max air flow	m³/h	720
Suction inlet	mm	120
Noise level (EN ISO 3744)	dB(A)	78
FILTER UNIT		
Filter Type		Star
Cleaning system		SELF CLEAN
Transport capacity	kg/h	160
VOLUME		
Dimensions	cm	170x74x200h
Weight	kg	440

#### All data mentioned in this document may change without notice Tutti i dati riportati in questo documento potrebbero variare senza avviso



## SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.

A pressure relief valve protects the motor, providing additional air for cooling.



The suction inlet is tangential, with an internally welded cyclone that deflects the incoming material.

The filter is equipped with a semiautomatic cleaning system handled by the operator. A pneumatic cylinder shakes the star filter by a vertical shaking movement which causes the detachment of dusts and wastes from the filter. This way, the operator will be able to decide without any limits when to turn the vacuum cleaner off and to clean the filter. The large surface star antistatic filter, located inside the filter chamber, is made of polyester and provides high resistance against clogging and passage of fine dust.

### COLLECTION UNIT

The vacuumed material is collected into a wheeled steel container, which can be extracted for easy disposal and can be used with optional disposable bags, for safer and handier disposal

# 

- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ PTFE COATED FILTER CLASS M
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST
- ✓ FLOOR FIXED SYSTEM, WITHOUT WHEELS
- ✓ REMOTE CONTROL