

DG VL 150 SE - INDUSTRIAL THREE PHASE



CEMENT



CERAMICS AND POTTERY INDUSTRIES



BUILDING AND CONSTRUCTION



- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- ✓ Largest surface filter in its category
- ✓ Integrated filter cleaning system
- ✓ Tangential suction inlet with integrated separation cyclone
- ✓ Pressure relief valve for motor protection
- ✓ Reduced downtime of machine tools
- ✓ Suitable for high specific weight material
- ✓ Fork lift intakes included
- ✓ Easily removable container for safe disposal of collected material



SUCTION UNIT

| | | |
|---------------------------|--------------------|-------------|
| Voltage | V - Hz | 400 - 50 3~ |
| Power | kW | 15 - 31,7 |
| Electrical protection | IP | 65 |
| Max water lift | mmH ₂ O | 6.000 |
| Max air flow | m ³ /h | 720 |
| Suction inlet | mm | 120 |
| Noise level (EN ISO 3744) | dB(A) | 78 |



FILTER UNIT

| | | |
|-----------------------|-----------------------------------|-------------------|
| Filter Type | | Star |
| Surface - Diameter | cm ² -mm | 70.000 - 560 |
| Material - Efficiency | IEC 60335-2-69 | Polyester - ANT M |
| Air load on filter | m ³ /m ² /h | 104 |
| Cleaning system | | SELF CLEAN |



COLLECTION UNIT

| | | |
|----------|---|-----|
| Capacity | l | 160 |
|----------|---|-----|



VOLUME

| | | |
|------------|----|-------------|
| Dimensions | cm | 170x74x200h |
| Weight | kg | 440 |



SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It is designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.

A pressure relief valve protects the motor, providing additional air for cooling.



FILTER UNIT

A vacuum gauge enables to check constantly the state of the filter and detect possible clogging, warning the operator that the filter must be cleaned.

The suction inlet is tangential, with an internally welded cyclone that deflects the incoming material.

The filter is equipped with a semiautomatic cleaning system handled by the operator. A pneumatic cylinder shakes the star filter by a vertical shaking movement which causes the detachment of dusts and wastes from the filter. This way, the operator will be able to decide without any limits when to turn the vacuum cleaner off and to clean the filter. The vacuum cleaner is equipped with a compressor which guarantees the autonomy of the machine.



COLLECTION UNIT

The vacuumed material is collected into a wheeled steel container, which can be extracted for easy disposal and can be used with optional disposable bags, for safer and handier disposal.

Forklift intakes for easy discharge.



OPTIONALS

- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ PTFE COATED FILTER CLASS M
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ REMOTE CONTROL
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST
- ✓ ATEX CERTIFICATION
- ✓ FLOOR FIXED SYSTEM, WITHOUT WHEELS
- ✓ EARTH GROUNDING