

DG VL 185 ACD - INDUSTRIAL THREE PHASE



AVIATION



FOOD INDUSTRY



OEM ORIGINAL EQUIPMENT



CEMENT



CHEMICAL-PHARMACEUTICAL



- ✓ Tangential suction inlet with integrated separation cyclone
- ✓ Complete steel construction
- ✓ Extractable collection container with optional use of disposable bags
- ✓ Pressure relief valve for motor protection
- ✓ Large surface antistatic filter
- ✓ Additional HEPA filter (99,995% on 0,18 micron) included
- ✓ SELF CLEAN filter-shaking cleaning system



SUCTION UNIT

Voltage	V - Hz	400 - 50 3~
Power	kW	18,5 - 35,6
Electrical protection	IP	65
Max water lift	mmH ₂ O	4.000
Max air flow	m ³ /h	1.350
Suction inlet	mm	120
Noise level (EN ISO 3744)	dB(A)	82



FILTER UNIT

Filter Type	Star	
Surface - Diameter	cm ² -mm	70.000 - 560
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Air load on filter	m ³ /m ² /h	192
Cleaning system	SELF CLEAN	



COLLECTION UNIT

Capacity	l	160
----------	---	-----



VOLUME

Dimensions	cm	170x74x200h
Weight	kg	450



SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It is designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.

A pressure relief valve protects the motor, providing additional air for cooling.



FILTER UNIT

An antistatic polyester star filter is placed inside the steel filter chamber. This filter protects the suction unit by preventing any spark which might be caused by electrostatic discharge.

A HEPA filter is included as standard (99,995% on 0,18 micron, class H) which holds the finest dusts and guarantees the cleanliness of the leaving air.

The filter is equipped with a self-cleaning system, controlled by the operator. A pneumatic cylinder shakes the filter cartridge, through a rapid vertical movement that causes the detachment of dust and materials possibly accumulated on the filter.



COLLECTION UNIT

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels, that make it suitable for mobile service even when used on rough surfaces.

The unit is manufactured with thick painted steel for improved sturdiness and long-lasting lifetime



OPTIONALS

- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER