

DM AIREX 25V 1/3D - AIR POWERED EXPLOSION PROOF







- ✓ Complete steel construction
- ✓ Extractable collection container with optional use of disposable bags
- ✓ Compact and mobile

- ✓ Easy filter replacement✓ Earth grounding
- ✓ Compressed air supply through a single Venturi suction unit

SUCTION UNIT		
Atex zones		ATEX Z20/21 Z1-2
Air supply	nlt / min	2.500
Air supply pressure	bar	6
Ø Air supply hose	mm	12
Max water lift	mmH⊡O	5.000
Max water lift	mmH00	5.000
Max air flow	m³/h	590
Noise level (EN ISO 3744)	dB(A)	74
Marking		II 1/3D Ex h IIIC T80°C Da/Dc

	Star
cm²-mm	30.000 - 500
IEC 60335-2-69	ANT Polyester - M - 1µm
	Manual

Transport capacity	kg/h	100
VOLUME		
Dimensions	cm	62X62X160h
Weight	kg	80

COPYRIGHT © 2023 DELFIN S.R.L. ALL RIGHTS RESERVED COPYRIGHT © 2023 DELFIN S.R.L. TUTTII DIRITTI RISERVATI



SUCTION UNIT

The suction is guaranteed by a multi-nozzle unit, protected inside a solid steel head, containing sound absorbing material that minimizes noise during service

FILTER UNIT

It is possible to clean the filter using an integrated mechanical system: an external lever shakes the filter vertically and enables to clean the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment. The large surface star antistatic filter, located inside the filter chamber, is made of polyester and provides high resistance against clogging and passage of fine dust.

S COLLECTION UNIT

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels , that make it suitable for mobile service even when used on rough surfaces. The vacuumed material is placed inside an AISI304 stainless steel drop-down bin mounted on wheels, which makes it possible to dispose easily and safely of the vacuumed material, if need be collecting it directly into a paper bag.

OPTIONALS

- ✓ ANTISTATIC FILTER CLASS M
- ✓ HEAT RESISTANT FILTER (UP TO 250° CELSIUS)
- ✓ STAINLESS STEEL COLLECTION TANK