







PHARMA 20.18 Z22 - INDUSTRIAL THREE PHASE



OEM ORIGINAL EQUIPMENT MANUFA



CHEMICAL-PHARMACEUTICAL



COFFEE, TEA, TOBACCO PROCESSING









- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- ✓ Low noise level
- ✓ Compact, silent, and flexible vacuum cleaner, ideal for suction on-board of machinery
- ✓ Star primary filter with integrated ergonomic cleaning system
- ✓ Optional H14 absolute filter for air blowing safety
- ✓ Compliant with EN 17348: DRY TYPE
- ✓ Side Channel Blower and Control Box Ex Dust Tight Certified

SUCTION UNIT		
Power	kW	2,2
Max water lift	mmH□O	3.000
Max air flow	m³/h	270
Suction inlet	mm	Clamp ø50 AlSl304
Noise level (EN ISO 3744)	dB(A)	70
Use zone		22 ATEX
Marking	II 3D Ex h tc IIIC T8	0°C (Int)/ T165°C (Ext) Dc
Atex zones		3D (20 int/22 ext)

FILTER UNIT		
Filter Type		Star
Surface - Diameter	cm²-mm	12.000 - 360
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Cleaning system		Manual

COLLECTION UNIT		
Capacity	I	22

VOLUME		
Dimensions	cm	70x51x129h
Weight	kg	75





SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.



FILTER UNIT

The large surface star antistatic filter, located inside the filter chamber, is made of polyester and provides high resistance against clogging and passage of fine dust.



COLLECTION UNIT

The unit is manufactured with thick painted steel for improved sturdiness and long-lasting lifetime



□ OPTIONALS

- ABSOLUTE HEPA FILTER /H14
- STAINLESS STEEL COLLECTION TANK
- STAINLESS STEEL TANK AND FILTER CHAMBER
- **EARTH GROUNDING**
- SAFE BAG SYSTEM FOR THE USE OF DISPOSABLE FILTER BAGS