

802 WD AIREX 14V 1/2D - 2/2G - AIR POWERED EXPLOSION PROOF




SHIPYARDS



ELECTRONICS



PACKAGING



- ✓ Vacuum gauge to detect filter clogging
- ✓ Compact and mobile
- ✓ Easy filter replacement
- ✓ Floating device to stop the suction when container is full
- ✓ Discharge hose for liquids
- ✓ Stainless steel AISI304 collection tank
- ✓ Earth grounding
- ✓ Powerful suction thanks to a multi-nozzle venturi unit



SUCTION UNIT

Atex zones		CE EX 1/2D
Max water lift	mmH ₂ O	3700
Max water lift	mmH ₂ O	3700
Max air flow	m ³ /h	300
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	68
Marking	II 1/2D Ex h IIC T85° Da/Db - II 2/2G Ex h IIB T6 Gb/Gb	



FILTER UNIT

Filter Type		Bag
Surface - Diameter	cm ² -mm	8.000 - 420
Material - Efficiency	IEC 60335-2-69	ANT Polyester - M - 1µm
Secondary filter		HEPA



COLLECTION UNIT

Transport capacity	kg/h	80
--------------------	------	----



VOLUME

Dimensions	cm	62x53x108h
Weight	kg	36



SUCTION UNIT

The suction is provided by a venturi compressed-air-driven suction unit, protected inside a strong steel chassis, which contains also sound absorbing material to minimize noise during service. The suction is developed by a venturi-type vented suction unit, protected inside a solid steel head, containing sound absorbing material that minimizes noise during service.



FILTER UNIT

A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.

A propylene filter for liquids is installed upstream. This filter guarantees the efficient filtration of the vacuumed oil; an additional plastic foam filter prevents most of the liquid mist from getting to the motor.

The dust filter is made of a double bag (polyester + nylon) and has a self cleaning system working on the pressure difference principle.



COLLECTION UNIT

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels, that make it suitable for mobile service even when used on rough surfaces.