



802 WD AIREX 7V 1/3D - AIR POWERED EXPLOSION PROOF



1	ELECTRONICS



- ✓ Vacuum gauge to detect filter clogging
- \checkmark Compact and mobile
- ✓ Easy filter replacement
- ✓ Floating device to stop the suction when container is full
- ✓ Discharge hose for liquids
- ✓ Powerful suction thanks to a multi-nozzle venturi unit

DRY

✓ Earth grounding

SUCTION UNIT		
Atex zones		ATEX Z20/21 Z1-2
Max water lift	mmH⊡O	3700
Max water lift	mmH00	3700
Max air flow	m³/h	150
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	68
Marking		ll 1/3D Ex h lllC T80°C Da/Dc

FILTER UNIT		
Filter Type		Bag
Surface - Diameter	cm²-mm	8.000 - 420
Material - Efficiency	IEC 60335-2-69	ANT Polyester - M - 1µm
Secondary filter		HEPA

COLLECTION UNIT

Transport capacity

VOLUME		
Dimensions	cm	62x53x108h
Weight	kg	36

kg/h

80



SUCTION UNIT

The suction is provided by a venturi compressed-air-driven suction unit, protected inside a strong steel chassis, which contains also sound absorbing material to minimize noise during service. The suction is developed by a venturi-type vented suction unit, protected inside a solid steel head, containing sound absorbing material that minimizes noise during service.

The head includes a pressure and a vacuum gauge, in order to detect the clogging of the filter



A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.

The dust filter is made of a double bag (polyester + nylon) and has a self cleaning system working on the pressure difference principle.

A propylene filter for liquids is installed upstream. This filter guarantees the efficient filtration of the vacuumed oil; an additional plastic foam filter prevents most of the liquid mist from getting to the motor.



The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels , that make it suitable for mobile service even when used on rough surfaces.

