

TECNOIL 220 - OIL AND CHIPS



METALWORKING



- ✓ Compact and mobile
- ✓ Complete steel construction
- ✓ Floating device to stop the suction when container is full
- ✓ Discharge hose for liquids
- ✓ Filtration and recovery of cutting oil and coolant liquid
- ✓ Discharge system through reverse flow by means of an hose. No need of discharge pump



SUCTION UNIT

Power	kW	3
Max water lift	mmH ₂ O	3.000/2.700
Max air flow	m ³ /h	318
Noise level (EN ISO 3744)	dB(A)	78



FILTER UNIT

Filter Type	3D SuperWeb + PPL
Media - Filtration	Polypropylene - 20µm



COLLECTION UNIT

Discharge system		
Liquids capacity	l	220
Solids capacity	l	40
Floating device		



VOLUME

Dimensions	cm	145x72x175h
Weight	kg	185



SUCTION UNIT

The suction is provided by three by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.



FILTER UNIT

A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.



COLLECTION UNIT

The vacuum cleaner is mounted on a solid steel trolley, provided with a support for hoses when not used, and equipped with oil proof wheels and braking castors.



OPTIONALS

- ✓ OIL & WATER PROOF CARTRIDGE
- ✓ PPL OIL FILTRATION KIT DOWN TO 300 MICRON (SUCTION)