

# DG VL 150 SE - INDUSTRIAL THREE PHASE



CEMENT



CERAMICS AND POTTERY INDUSTRIES



BUILDING AND CONSTRUCTION



- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- ✓ Largest surface filter in its category
- ✓ Integrated filter cleaning system
- ✓ Tangential suction inlet with integrated separation cyclone
- ✓ Pressure relief valve for motor protection
- ✓ Reduced downtime of machine tools
- ✓ Suitable for high specific weight material
- ✓ Fork lift intakes included
- ✓ Easily removable container for safe disposal of collected material

## SUCTION UNIT

Voltage	V - Hz	400 - 50 3~
Power	kW	17,3
Electrical protection	IP	65
Max water lift	mmH <sub>2</sub> O	6000
Max air flow	m <sup>3</sup> /h	720
Suction inlet	mm	120
Noise level (EN ISO 3744)	dB(A)	78

## FILTER UNIT

Filter Type		Star
Surface - Diameter	cm <sup>2</sup> -mm	70000 - 560
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Air load on filter	m <sup>3</sup> /m <sup>2</sup> /h	104
Cleaning system		SELF CLEAN

## COLLECTION UNIT

Discharge system		
Capacity	l	160

## VOLUME

Dimensions	cm	170x74x200h
Weight	kg	440

COPYRIGHT © 2023 DELFIN S.R.L. ALL RIGHTS RESERVED  
COPYRIGHT © 2023 DELFIN S.R.L. TUTTI I DIRITTI RISERVATI



## SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It is designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.

A pressure relief valve protects the motor, providing additional air for cooling.



## FILTER UNIT

A vacuum gauge enables to check constantly the state of the filter and detect possible clogging, warning the operator that the filter must be cleaned.

The suction inlet is tangential, with an internally welded cyclone that deflects the incoming material.

The filter is equipped with a semiautomatic cleaning system handled by the operator. A pneumatic cylinder shakes the star filter by a vertical shaking movement which causes the detachment of dusts and wastes from the filter. This way, the operator will be able to decide without any limits when to turn the vacuum cleaner off and to clean the filter. The vacuum cleaner is equipped with a compressor which guarantees the autonomy of the machine.



## COLLECTION UNIT

The vacuumed material is collected into a wheeled steel container, which can be extracted for easy disposal and can be used with optional disposable bags, for safer and handier disposal.

Forklift intakes for easy discharge.



## OPTIONALS

- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ PTFE COATED FILTER CLASS M
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ REMOTE CONTROL
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST
- ✓ ATEX CERTIFICATION
- ✓ FLOOR FIXED SYSTEM, WITHOUT WHEELS
- ✓ EARTH GROUNDING